

**SUBMERSIBLE PUMPSET FOR 150mm BOREWELL
(V6 -140mm OD) RADIAL FLOW**

MODEL: DR60 BORE: 150mm (6") OUTLET : 50mm (2")

Model / Stages	HP	Discharge LPM	0	50	75	100	125	150	175
DR60 / 6	2.0		56	51	48	42	36	30	22
DR60 / 8	2.0		72	64	58	50	42	33	24
DR60 / 10	3.0		93	85	80	70	60	50	37
DR60 / 12	3.0		108	96	87	75	63	49	36
DR60 / 16	4.0		144	128	116	100	84	66	48
DR60 / 20	5.0		180	160	145	125	105	82	60
DR60 / 25	5.0		220	190	172	145	120	88	64
DR60 / 20	6.0		187	170	160	140	120	100	75
DR60 / 24	6.0		216	192	174	150	126	98	72
DR60 / 25	6.0	Total Head in Metres	225	200	181	156	131	102	75
DR60 / 25	7.5		233	212	200	175	150	125	94
DR60 / 28	7.5		252	224	202	175	147	115	84
DR60 / 29	7.5		270	240	217	187	157	123	90
DR60 / 35	7.5		290	260	240	210	160	120	80
DR60 / 35	10.0		315	280	254	219	184	143	105
DR60 / 36	10.0		324	288	261	225	189	148	108
DR60 / 40	10.0		355	324	308	266	224	182	130
DR60 / 40	12.5		373	340	320	280	240	200	150
DR60 / 45	15.0		420	382	360	315	270	225	169
DR60 / 50	15.0		466	424	400	350	300	250	188

MODEL: DR60H BORE: 150mm (6") OUTLET : 50mm (2")

Model / Stages	HP	Discharge LPM	0	25	40	60	80	100	120
DR60H / 8	3.0		112	106	100	93	85	72	53
DR60H / 10	4.0		140	133	125	117	107	90	66
DR60H / 12	5.0		168	160	150	140	128	109	80
DR60H / 15	6.0	Total Head in Metres	210	200	188	175	160	136	100
DR60H / 20	7.5		280	266	250	234	214	180	134
DR60H / 25	10.0		348	333	313	291	267	227	167
DR60H / 29	12.5		420	400	376	350	320	272	200

MODEL: DR61 BORE: 150mm (6") OUTLET : 50mm (2")

Model / Stages	HP	Discharge LPM	0	100	125	150	175	200	225
DR61 / 4	3.0		44	40	38	35	30.5	27.5	24.5
DR61 / 6	3.0		65	60	57	52	45.5	41	37
DR61 / 8	4.0		87	80	76	69	61	55	49
DR61 / 10	5.0		109	100	95	87	76	68.5	61
DR61 / 12	6.0	Total Head in Metres	131	120	114	105	91.5	82.5	73.5
DR61 / 15	7.5		163	150	142	130	114	103	91.5
DR61 / 16	7.5		174	160	152	138.5	121.5	110	98
DR61 / 20	10.0		217	200	190	173	152	137	122
DR61 / 25	12.5		272	250	238	216	190	171.5	152.5
DR61 / 29	15.0		315	290	275.5	254	221	199	177

**SUBMERSIBLE PUMPSET FOR 150mm BOREWELL
(V6 -140mm OD) RADIAL FLOW**

MODEL: DR62 BORE: 150mm (6")

OUTLET : 50mm (2")

Model / Stages	HP	Discharge LPM	0	50	75	100	125	150	175
DR62 / 4	2.0		41	37	35	33	29	24	19
DR62 / 6	2.0		59	54	50	48	43	35	27
DR62 / 6	3.0		62	56	52	50	45	37	28
DR62 / 8	3.0		81	75	70	66	58	49	37
DR62 / 10	3.0		99	91	84	80	71	59	45
DR62 / 10	4.0		101	94	87	82	73	61	46
DR62 / 12	4.0		119	109	101	96	85	71	54
DR62 / 12	5.0		124	112	104	99	89	73	56
DR62 / 15	5.0		148	137	128	121	107	89	68
DR62 / 16	5.0		151	142	132	125	110	92	72
DR62 / 16	6.0		157	147	137	129	114	95	73
DR62 / 18	7.5	Total Head in Metres	186	168	156	149	134	110	84
DR62 / 20	7.5		194	182	172	161	146	127	105
DR62 / 25	10.0		216	203	192	178	163	140	113
DR62 / 29	10.0		266	244	230	213	195	168	136
DR62 / 29	12.5		298	272	258	241	219	190	157
DR62 / 35	12.5		310	285	268	249	228	196	158
DR62 / 35	15.0		335	318	301	281	255	223	183
DR62 / 40	15.0		388	364	344	322	292	254	210
DR62 / 40	17.5		414	374	347	330	297	244	187
DR62 / 50	17.5		492	450	417	400	359	292	225
DR62 / 45	20.0		432	409	387	362	328	286	236
DR62 / 50	20.0		505	470	435	410	365	305	230

MODEL: DR62H BORE: 150mm (6")

OUTLET : 50mm (2")

Model / Stages	HP	Discharge LPM	0	50	75	100	125	150	175
DR62H / 8	4.0		115	108	101	90	80	70	56
DR62H / 10	5.0		144	133	126	112	100	88	70
DR62H / 12	6.0		173	160	151	134	120	106	84
DR62H / 15	7.5		216	200	189	168	150	132	105
DR62H / 20	10.0	Total Head in Metres	288	266	252	224	200	176	140
DR62H / 25	12.5		360	332	315	280	250	220	175
DR62H / 29	15.0		430	399	378	336	300	264	210
DR62H / 35	17.5		503	465	441	392	350	308	245
DR62H / 40	20.0		575	532	504	448	400	352	280

MODEL: DR63 BORE: 150mm (6")

OUTLET : 50mm (2")

Model / Stages	HP	Discharge LPM	0	125	150	180	200	230	250
DR63 / 4	3.0		43	40	39	37	35	31	27
DR63 / 5	3.0		50	47	46	45	41	36	32
DR63 / 6	4.0		68	59	58	56	52	45	40
DR63 / 8	5.0		85	79	78	75	69	61	54
DR63 / 8	6.0		86	80	79	76	70	62	55
DR63 / 10	6.0		107	99	97	94	86	76	67
DR63 / 10	7.5	Total Head in Metres	108	100	98	95	87	77	68
DR63 / 12	7.5		128	119	116	113	103	91	80
DR63 / 14	10.0		149	138	135	131	120	106	93
DR63 / 16	10.0		170	158	154	150	137	121	106
DR63 / 16	12.5		171	159	155	151	138	122	107
DR63 / 18	12.5		191	177	173	168	154	136	119
DR63 / 20	12.5		212	197	192	187	171	151	132

**SUBMERSIBLE PUMPSET FOR 150mm BOREWELL
(V6 -140mm OD) RADIAL FLOW**

MODEL: DR63 BORE: 150mm (6") OUTLET : 50mm (2")

Model / Stages	HP	Discharge LPM	0	125	150	180	200	230	250
DR63 / 24	12.5	Total Head in Metres	254	236	230	224	205	181	158
DR63 / 24	15.0		255	237	231	225	206	182	159
DR63 / 25	17.5		265	246	240	233	214	189	165
DR63 / 30	17.5		300	282	276	270	246	216	192
DR63 / 32	20.0		340	316	308	300	274	242	212

MODEL: DR64 BORE: 150mm (6") OUTLET : 50mm (2")

Model / Stages	HP	Discharge LPM	0	200	250	300	350	400	450
DR64 / 4	4.0	Total Head in Metres	45	40	39	35	32	25	17
DR64 / 5	5.0		57	51	49	44	40	32	22
DR64 / 6	5.0		70	62	59	53	48	39	27
DR64 / 6	6.0		71	63	60	54	49	40	28
DR64 / 8	7.5		92	82	78	71	64	52	36
DR64 / 10	10.0		116	103	98	89	80	65	45
DR64 / 12	10.0		138	123	117	107	96	78	54
DR64 / 12	12.5		139	124	118	108	97	79	55
DR64 / 14	12.5		162	144	137	125	112	91	63
DR64 / 16	15.0		183	163	155	142	127	104	72
DR64 / 18	17.5		206	183	174	160	143	117	81
DR64 / 20	17.5		212	188	175	162	145	119	83
DR64 / 20	20.0		232	206	198	178	160	130	90



**SUBMERSIBLE PUMPSET FOR 150mm BOREWELL
(V6 – 140mm OD) MIXED FLOW**

MODEL: DM60 BORE: 150mm (6")

OUTLET : 65mm (2.5")

Model / tages	HP	Discharge LPM	0	150	200	275	350	425	500
DM60 / 5	5.0		60	57	55	50	40.5	30	17.5
DM60 / 6	6.0		72	68.5	66	60	49	36	21
DM60 / 8	7.5		96	91	88	80	65	48	28
DM60 / 10	10.0	Total Head in Metres	120	114	110	100	81	60	35
DM60 / 12	12.5		144	137	132	120	97.5	72	42
DM60 / 15	15.0		180	171	165	150	122	90	52.5
DM60 / 18	17.5		216	205	198	180	146	108	63
DM60 / 20	20.0		240	228	220	200	162.5	120	70

MODEL: DM61 BORE: 150mm (6")

OUTLET : 65mm (2.5")

Model / Stages	HP	Discharge LPM	0	200	300	400	500	600	700
DM61 / 4	5.0		47	43	39	34	30	24	17
DM61 / 5	6.0		58	53	49	43	38	30	21
DM61 / 6	7.5		70	64	59	52	45	36	25
DM61 / 8	10.0	Total Head in Metres	94	85	78	69	60	48	33
DM61 / 10	12.5		118	107	98	86	75	60	42
DM61 / 12	15.0		141	128	117	103	90	72	50
DM61 / 14	17.5		164	149	137	120	105	84	58
DM61 / 16	20.0		188	171	156	137	120	96	67
DM61 / 18	22.5		211	192	175	154	135	108	75

MODEL: DM62 BORE: 150mm (6")

OUTLET : 65mm (2.5")

Model / Stages	HP	Discharge LPM	0	300	400	500	600	700	800
DM62 / 3	5.0		34	29	27	24	21	17	13
DM62 / 4	6.0		46	42	38	34	30	25	19
DM62 / 5	7.5		58	52	47	42	36	31	24
DM62 / 6	10.0		71	62	56	50	43	37	29
DM62 / 7	10.0	Total Head in Metres	80	74	67	60	52	44	34
DM62 / 7	12.5		81	75	68	61	53	45	35
DM62 / 8	12.5		92	84	76	68	60	50	38
DM62 / 9	12.5		103	95	86	77	66	56	43
DM62 / 9	15.0		104	96	87	78	67	57	44
DM62 / 10	15.0		114	103	94	84	73	62	47
DM62 / 12	20.0		138	126	114	102	88	75	58
DM62 / 14	22.5		161	148	134	120	104	88	68
DM62 / 16	25.0		185	172	154	137	120	100	67

MODEL: DM63 BORE: 150mm (6")

OUTLET : 80mm(3")

Model / Stages	HP	Discharge LPM	0	300	400	500	600	700	800
DM63 / 3	5.0		34	31	29	26	24	21	17
DM63 / 4	6.0		46	42	39	35	32	28	22
DM63 / 5	7.5		57	52	49	44	40	35	29
DM63 / 6	10.0		68	62	58	52	47	42	34
DM63 / 7	12.5	Total Head in Metres	79	73	68	62	56	50	41
DM63 / 8	15.0		91	83	78	70	64	57	47
DM63 / 9	15.0		103	94	88	80	72	63	50
DM63 / 10	17.5		114	104	97	88	81	70	58
DM63 / 12	22.5		137	125	116	105	97	84	70
DM63 / 14	25.0		160	146	135	122	113	98	81

**SUBMERSIBLE PUMPSET FOR 150mm BOREWELL
(V6 – 140mm OD) MIXED FLOW**

MODEL: DM64 BORE: 150mm (6")

OUTLET : 80mm(3")

Model / Stages	HP	Discharge LPM	0	500	600	750	900	1000	1100
DM64 / 2	5.0		20	17	16	15	13	11	7
DM64 / 3	7.5		31	28	27	25	22	19	12
DM64 / 4	7.5		41	37	35	33	29	26	16
DM64 / 4	10.0		42	38	36	34	30	27	17
DM64 / 5	10.0		51	45	43	41	35	31	20
DM64 / 5	12.5		52	46	44	42	36	32	20
DM64 / 6	12.5	Total Head in Metres	62	56	54	51	44	39	25
DM64 / 6	15.0		63	57	55	52	45	40	26
DM64 / 7	15.0		72	65	63	60	51	45	29
DM64 / 7	17.5		73	66	64	61	52	46	30
DM64 / 8	17.5		82	74	72	68	58	52	33
DM64 / 8	20.0		83	75	73	69	59	53	34
DM64 / 9	20.0		93	84	81	76	66	58	37
DM64 / 9	22.5		94	85	82	77	67	59	38
DM64 / 10	25.0	105	95	92	87	75	66	42	

MODEL: DM65 BORE: 150mm (6")

OUTLET : 80mm(3") / OUTLET :100mm(4")

Model / Stages	HP	Discharge LPM	0	650	800	900	1000	1200	1300
DM65 / 1	3.0		12	10	9	8	7	6	5
DM65 / 2	6.0		22	19	18	17	16	13	10
DM65 / 3	10.0		34	29	27	25	24	20	15
DM65 / 4	10.0		44	39	36	34	32	26	20
DM65 / 4	12.5	Total Head in Metres	45	40	37	35	33	27	21
DM65 / 5	12.5		57	49	45	43	40	33	25
DM65 / 5	15.0		58	50	46	44	41	34	26
DM65 / 6	15.0		68	59	54	51	48	39	30
DM65 / 6	17.5		69	60	55	52	49	40	31
DM65 / 7	17.5		80	68	63	60	56	46	35
DM65 / 7	20.0		81	69	64	61	57	47	36
DM65 / 8	25.0		92	78	72	68	64	52	40